Sealed Liquid Cells - Model SL-4 Heavy Duty

SL-4 cell offers a heavy duty, corrosion resistant sealed liquid spectrophotometer cell designed to withstand rough handling and continuous sampling in laboratories. The large 25mm circular aperture is suitable for use with both dispersive and FTIR instruments.

| ltem # | Item Name | Pathlength | Material | |
|-----------------------------------|---|------------|----------|--|
| | | 0.015 mm | | |
| | | 0.025 mm | | 170 |
| | | 0.05 mm | | -0- |
| 0005A-1965W | Model SL-4 NaCl Heavy Duty Sealed Liquid Cell | 0.1 mm | NaCl | Section Street Street |
| | | 0.2 mm | | Replacement Crystals |
| | | 0.5 mm | | <u>39.5mm x 39.5mm x</u> <u>6.5mm</u> |
| | | 1.0 mm | | 0.511111 |
| | | 0.015 mm | | |
| | | 0.025 mm | | Replacement Cell Parts |
| | | 0.05 mm | | |
| <u>0005B-1972W</u> 0005C-1979W | Model SL-4 KCl Heavy Duty Sealed Liquid Cell | 0.1 mm | KCI | |
| | | 0.2 mm | | |
| | | 0.5 mm | | |
| | | 1.0 mm | | |
| | | 0.015 mm | | Replacement Cell Part |
| | | 0.025 mm | | |
| | | 0.025 mm | | |
| | Madal CL 6 //Pattana Data Castad Linuid Call | | 1/D- | |
| | Model SL-4 KBr Heavy Duty Sealed Liquid Cell | 0.1 mm | KBr | |
| | | 0.2 mm | | |
| | | 0.5 mm | | |
| | | 1.0 mm | | |
| | | 0.015 mm | | |
| | | 0.025 mm | | |
| <u>0005D-1986W</u> | | 0.05 mm | | |
| | Model SL-4 CaF2 Heavy Duty Sealed Liquid Cell | 0.1 mm | CaF2 | |
| | | 0.2 mm | | |
| | | 0.5 mm | | |
| | | 1.0 mm | | |
| | | 0.015 mm | | |
| | | 0.025 mm | | |
| | | 0.05 mm | | |
| <u>0005E-1993W</u> | Model SL-4 BaF2 Heavy Duty Sealed Liquid Cell | 0.1 mm | BaF2 | |
| | | 0.2 mm | | |
| | | 0.5 mm | | |
| | | 1.0 mm | | |
| | | 0.015 mm | | |
| | | 0.025 mm | | |
| | | 0.05 mm | | |
| <u>0005J-7435W</u> | Model SL-4 ZnSe Heavy Duty Sealed Liquid Cell | 0.1 mm | ZnSe | |
| | | 0.2 mm | | |
| | | 0.5 mm | | |
| | | 1.0 mm | | |

Dimension des fenêtres : 39.5mm x 39.5mm x 6.5mm



JASCO France 17 Rue des Cerisiers 91090 Lisses - France

Tél. 01 64 97 09 60 Fax: 01 85 09 90 76 email: jascofrance@jascofrance.fr

Replacement parts :

| 0001-3722 | Neoprene Gaskets - 39.5mmx39.5mm, pk/4 |
|-------------------------|--|
| 0010-186 | Cell Reconditioning- Calibration of Liquid Cell |
| 0010-185 | Cell Reconditioning- Calibration and Matching of .05, 0.1, 0.2, 0.5 and 1mm Liquid Cells |
| 0010-4170 pathlength | Cell Reconditioning- Calibration and Matching of Liquid Cells with 0.015mm or 0.025mm |
| 0005-4294 | Replacement Screw for SL-4 Cell |

0005-4295 Luer Lock Syringe Fitting (Female)- for SL-4 Cell



JASCO France 17 Rue des Cerisiers 91090 Lisses - France

Tél. 01 64 97 09 60 Fax: 01 85 09 90 76 email: jascofrance@jascofrance.fr